




BOLD TWIST 075 | CARPET 400 CM

PRODUCT SPECIFICATIONS

Surface structure	DIN ISO 2424		Bouclé
Pile material	DIN ISO 2424		100% Econyl (gerecyclede polyamide) SD
(Secondary) backing	DIN ISO 2424		AB felt
Number of tufts	ISO 1763		19500 p/m ²
Total weight	ISO 8543		3000 g/m ²
Total height	ISO 1765		8.1 mm
Pile weight	DIN ISO 2424		1500 g/m ²
Pile height	ISO 1766		2.5 mm
Design			Gemêleerd

PERFORMANCE SPECIFICATIONS

Comfort level	EN 1307		LC2
Usage classification	EN 1307		32 - normal project use
Castor chair test	EN 985		Suitable for office chairs with castors
Slip resistance	EN 13893 DIN 51130		Antislip
Usage on stairs			Suitable for stairs
Light fastness	DIN EN ISO 105 B02		≥ 5
Water fastness	DIN EN ISO 105 E01		5
Resistance to abrasion dry/wet	DIN EN ISO 105 X12		4-5

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leox.com | I www.leox.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

Antistatic

ISO 6356



Permanent antistatisch

TECHNICAL SPECIFICATIONS

Flammability

DIN EN 13501



Cfl-s1

Thermal resistance

ISO 8302



0.12 m² K/W

Impact sound insulation

ISO 10140



22 dB

Static electrical propensity

ISO 6356



≤ 2.0 kV

Acoustical absorption

ISO 11654

0.25 α_w

Sound absorption 125 Hz

ISO 354

0 as

Sound absorption 250 Hz

ISO 354

0.05 as

Sound absorption 500 Hz

ISO 354

0.15 as

Sound absorption 1000 Hz

ISO 354

0.35 as

Sound absorption 2000 Hz

ISO 354

0.3 as

Sound absorption 4000 Hz

ISO 354

0.35 as

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions

EN 717-1



Complies with European E1 standard (European chamber method EN 717-1)

GuT



GuT-gecertificeerd

VOC emissions

REACH gecertificeerd

CO₂ neutral

Ja

Recyclable



Ja

CE



CE

PRODUCT OPTIONS

XXtra Care



We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

LAYING DIRECTION

LEOXX B.V.

Sasdiijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leox.com | I www.leox.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)