



BOLD TWIST 845 | CUSTOM RUG

PRODUCT SPECIFICATIONS

|                     |              |                                                                                                                          |
|---------------------|--------------|--------------------------------------------------------------------------------------------------------------------------|
| Surface structure   | DIN ISO 2424 | Bouclé                                                                                                                   |
| Pile material       | DIN ISO 2424 |  100% Econyl (gerecyclede polyamide) SD |
| Finishing           |              | Maatwerk                                                                                                                 |
| (Secondary) backing | DIN ISO 2424 | AB felt                                                                                                                  |
| Number of tufts     | ISO 1763     | 19500 p/m²                                                                                                               |
| Total weight        | ISO 8543     |  3000 g/m²                            |
| Total height        | ISO 1765     |  8.1 mm                               |
| Pile weight         | DIN ISO 2424 | 1500 g/m²                                                                                                                |
| Pile height         | ISO 1766     | 2.5 mm                                                                                                                   |
| Design              |              | Gemêleerd                                                                                                                |

PERFORMANCE SPECIFICATIONS

|                                |                    |                                                                                                                             |
|--------------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Comfort level                  | EN 1307            |  LC2                                     |
| Usage classification           | EN 1307            |  32 - normal project use                 |
| Castor chair test              | EN 985             |  Suitable for office chairs with castors |
| Slip resistance                | EN 13893 DIN 51130 |  Antislip                                |
| Light fastness                 | DIN EN ISO 105 B02 |  ≥ 5                                     |
| Water fastness                 | DIN EN ISO 105 E01 |  5                                       |
| Resistance to abrasion dry/wet | DIN EN ISO 105 X12 | 4-5                                                                                                                         |

Antistatic

ISO 6356



Permanent antistatisch

## TECHNICAL SPECIFICATIONS

|                              |              |  |             |
|------------------------------|--------------|--|-------------|
| Flammability                 | DIN EN 13501 |  | Cfl-s1      |
| Thermal resistance           | ISO 8302     |  | 0.12 m² K/W |
| Impact sound insulation      | ISO 10140    |  | 22 dB       |
| Static electrical propensity | ISO 6356     |  | ≤ 2.0 kV    |
| Acoustical absorption        | ISO 11654    |  | 0.25 αω     |
| Sound absorption 125 Hz      | ISO 354      |  | 0 as        |
| Sound absorption 250 Hz      | ISO 354      |  | 0.05 as     |
| Sound absorption 500 Hz      | ISO 354      |  | 0.15 as     |
| Sound absorption 1000 Hz     | ISO 354      |  | 0.35 as     |
| Sound absorption 2000 Hz     | ISO 354      |  | 0.3 as      |
| Sound absorption 4000 Hz     | ISO 354      |  | 0.35 as     |

## ENVIRONMENTAL SPECIFICATIONS

|                         |          |  |                                                                       |
|-------------------------|----------|--|-----------------------------------------------------------------------|
| Formaldehyde emissions  | EN 717-1 |  | Complies with European E1 standard (European chamber method EN 717-1) |
| GuT                     |          |  | GuT-gecertificeerd                                                    |
| VOC emissions           |          |  | REACH gecertificeerd                                                  |
| CO <sub>2</sub> neutral |          |  | Ja                                                                    |
| Recyclable              |          |  | Ja                                                                    |
| CE                      |          |  | CE                                                                    |

## PRODUCT OPTIONS

|            |  |                                                                                                                                                                                                                                                              |
|------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| XXtra Care |  | We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor. |
|------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

LEOXX reserves the right to make technical adjustments that lead to quality improvement.

## LEOXX B.V.

Sasdiijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leox.com | I www.leox.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01



[View product](#)