




BOUCLÉ MIX 363 | CUSTOM RUG

PRODUCT SPECIFICATIONS

Surface structure	DIN ISO 2424	Bouclé
Pile material	DIN ISO 2424	100% polyamide PA 6.6 Piece Dyed
Finishing		Maatwerk
(Secondary) backing	DIN ISO 2424	Action back
Gauge		1/10
Number of tufts	ISO 1763	185700 p/m²
Total weight	ISO 8543	 1690 g/m²
Total height	ISO 1765	 5.1 mm
Pile weight	DIN ISO 2424	750 g/m²
Pile height	ISO 1766	2.9 mm
Design		Gemêleerd

PERFORMANCE SPECIFICATIONS

Comfort level	EN 1307	 LC2
Usage classification	EN 1307	 33 - heavy project use
Castor chair test	EN 985	 Suitable for office chairs with castors
Fray resistant		 Rafelt niet bij het versnijden
Slip resistance	EN 13893 DIN 51130	 Antislip
Light fastness	DIN EN ISO 105 Bo2	 ≥ 5

Water fastness	DIN EN ISO 105 E01		≥ 4
Resistance to abrasion dry/wet	DIN EN ISO 105 X12		≥ 4
Antistatic	ISO 6356		Permanent antistatisch

TECHNICAL SPECIFICATIONS

Horizontal resistance	ISO 10965		$\leq 10^{-10} \Omega$
Static electrical propensity	EN 1815		$\leq 2.0 \text{ kV}$
Vertical resistance	ISO 10965		$\leq 10^{-10} \Omega$
Flammability	DIN EN 13501		Cfl-s1
Thermal resistance	ISO 8302		$\leq 0.15 \text{ m}^2 \text{ K/W}$
Impact sound insulation	ISO 10140		22 dB
Acoustical absorption	ISO 11654		0.10 α_w
Sound absorption 125 Hz	ISO 354		-0.01 α_s
Sound absorption 250 Hz	ISO 354		0 α_s
Sound absorption 500 Hz	ISO 354		0.06 α_s
Sound absorption 1000 Hz	ISO 354		0.1 α_s
Sound absorption 2000 Hz	ISO 354		0.24 α_s
Sound absorption 4000 Hz	ISO 354		0.39 α_s

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1		Complies with European E1 standard (European chamber method EN 717-1)
GuT			GuT-gecertificeerd
VOC emissions		 	A+ émissions dans l'air intérieur M1
CO ₂ neutral			Ja
Recyclable			Ja
CE			CE

PRODUCT OPTIONS

LEOXX B.V.

Sasdiijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leoxx.com | I www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

XXtra Care



We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | **E** info@leoxx.com | **I** www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01