




CRISP ADAM | BROADLOOM 200 CM ACOUSTIC

PRODUCT SPECIFICATIONS		
Surface structure		Jacquard geweven luspool
(Secondary) backing	DIN ISO 2424	Acoustic felt (93% PET)
Number of tufts	ISO 1763	0 p/m²
Total weight	ISO 8543	 3330 g/m²
Total height	ISO 1765	 5.2 mm
Composition		50% mineral - 13% recycled - 37% primary fossil content (top layer with fiberglass reinforcing core)
Manufacturation process		Jacquard geweven
Design		Sleets

PERFORMANCE SPECIFICATIONS		
Usage classification	EN 1307	 33 - heavy project use
Castor chair test	EN 985	 Suitable for office chairs with castors
Fray resistant		 Rafelt niet bij het versnijden
Slip resistance	EN 13893 DIN 51130	 R10
Usage on stairs		 Suitable for stairs
Antistatic	EN 1815	 Permanent antistatisch
Light fastness	DIN EN ISO 105 B02	 ≥ 7
Dimensional stability	EN 986	 < 0.2%

Light Reflectance Value (LRV - Y)



9.6

TECHNICAL SPECIFICATIONS

Static electrical propensity

EN 1815



< 2.0 kV

Flammability

DIN EN 13501



Bfl-s1

Thermal resistance

ISO 8302



ca. 0.0680 m² K/W

Impact sound insulation

ISO 10140



22 dB

Acoustical absorption

ISO 11654



0.15 αω

Sound absorption 125 Hz

ISO 354

0 as

Sound absorption 250 Hz

ISO 354

0.03 as

Sound absorption 500 Hz

ISO 354

0.08 as

Sound absorption 1000 Hz

ISO 354

0.08 as

Sound absorption 2000 Hz

ISO 354

0.08 as

Sound absorption 4000 Hz

ISO 354

0.1 as

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions

EN 717-1



Complies with REACH

Complies with European E1 standard (European chamber method EN 717-1)

The Blue Angel



Conform Blauer Engel-normering

Phthalate free

Yes

VOC emissions



A+ émissions dans l'air intérieur



Floorscore



Indoor Air Comfort Gold



M1

CO₂ neutral

Ja

Recyclable



Ja

CE



CE

PRODUCT OPTIONS

LEOXX B.V.

Sasdiijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leoxx.com | I www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

XXtra Care



We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | **E** info@leoxx.com | **I** www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01