



FINE LINES 181 | TILE 50 X 50 CM

PRODUCT SPECIFICATIONS

Surface structure	DIN ISO 2424	Vlakweef
Pile material	DIN ISO 2424	100% polyamide 6 Solution Dyed
Number of tufts	ISO 1763	164000 p/m²
Total weight	ISO 8543	 3100 g/m²
Total height	ISO 1765	 4.5 mm
Pile weight	DIN ISO 2424	400 g/m²
Pile height	ISO 1766	2 mm
Design		Lineair

PERFORMANCE SPECIFICATIONS

Comfort level	EN 1307	 LC1
Usage classification	EN 1307	 33 - heavy project use
Castor chair test	EN 985	 Suitable for office chairs with castors
Fray resistant		 Rafelt niet bij het versnijden
Slip resistance	EN 13893 DIN 51130	 Antislip
Antistatic	ISO 6356	 Permanent antistatisch
Dimensional stability	EN 986	 Falls within norms

TECHNICAL SPECIFICATIONS

Flammability	DIN EN 13501		Bfl-s1
Thermal resistance	ISO 8302		ca 0.10 m² K/W
Impact sound insulation	ISO 10140		20 dB
Static electrical propensity	ISO 6356		≤ 2.0 kV
Acoustical absorption	ISO 11654		0.20 α _w

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1		Complies with European E1 standard (European chamber method EN 717-1)
GuT			GuT-gecertificeerd
VOC emissions		 	Indoor Air Comfort Gold M1
CO ₂ neutral			Ja
Recyclable			Ja
CE			CE

PRODUCT OPTIONS

XXtra Care		We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.
------------	---	--

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leoxx.com | I www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01



[View product](#)