



PURLINE 1500 PEI390 | HALIFAX OAK  
BROWN | INTERNAL CORNER

PRODUCT SPECIFICATIONS

|                         |                                                                                                                                                                                                                    |                                                                                   |           |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------|
| Surface structure       | Fine wooden pore                                                                                                                                                                                                   |                                                                                   |           |
| Total weight            | EN ISO 24340 (EN 429)                                                                                                                                                                                              |  | 3400 g/m² |
| Total thickness         | EN ISO 24346 (EN 428)                                                                                                                                                                                              |  | 2.5 mm    |
| Composition             | Heterogeneous with ecuran as the main component; a high-performance composite material made primarily from vegetable oils such as rapeseed or castor oil and naturally occurring mineral components such as chalk. |                                                                                   |           |
| Manufacturation process | Calender process                                                                                                                                                                                                   |                                                                                   |           |
| Design                  | Hout                                                                                                                                                                                                               |                                                                                   |           |

PERFORMANCE SPECIFICATIONS

|                                   |                      |                                                                                                                                                                            |                                                    |
|-----------------------------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Dimensional stability             | EN ISO 23999         |                                                                                         | ≤ 0.15%                                            |
| Residual indentation              | EN ISO 24343-1       |                                                                                         | ≤ 0.10 mm                                          |
| Slip resistance                   | EN 13893 DIN 51130   |                                                                                         | R9                                                 |
| Antistatic                        | EN 1815              |                                                                                         | Permanent antistatisch                             |
| Light fastness                    | DIN EN ISO 105 B02   |                                                                                         | ≥ 7                                                |
| Usage classification              | EN ISO 10874 EN 685  | <br> | 34<br>43                                           |
| Castor chair test (Type W)        | EN ISO 4918 (EN 425) |                                                                                         | Geschikt voor bureaustoelen met zachte zwenkwielen |
| Light Reflectance Value (LRV - Y) |                      |                                                                                         | 19.8                                               |

## TECHNICAL SPECIFICATIONS

|                              |              |                                                                                   |                 |
|------------------------------|--------------|-----------------------------------------------------------------------------------|-----------------|
| Static electrical propensity | EN 1815      |  | ≤ 2.0 kV        |
| Flammability                 | DIN EN 13501 |  | Cfl-s1          |
| Thermal resistance           | ISO 8302     |  | ca. 0.01 m² K/W |

## ENVIRONMENTAL SPECIFICATIONS

|                         |          |                                                                                                                                                                                                                                                             |                                                                       |
|-------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Formaldehyde emissions  | EN 717-1 |                                                                                                                                                                            | Complies with European E1 standard (European chamber method EN 717-1) |
| The Blue Angel          |          |                                                                                                                                                                            | Ja                                                                    |
| Phthalate free          |          |                                                                                                                                                                                                                                                             | Yes                                                                   |
| VOC emissions           |          | <br><br> | A+ émissions dans l'air intérieur<br>Floorscore<br>M1                 |
| CO <sub>2</sub> neutral |          |                                                                                                                                                                           | Ja                                                                    |
| Recyclable              |          |                                                                                                                                                                          | Ja                                                                    |
| CE                      |          |                                                                                                                                                                          | CE                                                                    |

## PRODUCT OPTIONS

|            |                                                                                     |                                                                                                                                                                                                                                                              |
|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| XXtra Care |  | We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor. |
|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.

## LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E [info@leoxx.com](mailto:info@leoxx.com) | I [www.leoxx.com](http://www.leoxx.com)

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01



[View product](#)