



PURLINE 1500 PSo14 | SUMMER SKY |  
WELDING RODS

PRODUCT SPECIFICATIONS

|                         |                       |                                                                                   |                  |
|-------------------------|-----------------------|-----------------------------------------------------------------------------------|------------------|
| Total thickness         | EN ISO 24346 (EN 428) |  | 4.0 mm           |
| Composition             |                       |                                                                                   | PE               |
| Manufacturation process |                       |                                                                                   | Calender process |
| Design                  |                       |                                                                                   | Uni              |

PERFORMANCE SPECIFICATIONS

|                                   |                      |                                                                                     |                                                    |
|-----------------------------------|----------------------|-------------------------------------------------------------------------------------|----------------------------------------------------|
| Dimensional stability             | EN ISO 23999         |  | ≤ 0.15%                                            |
| Residual indentation              | EN ISO 24343-1       |  | ≤ 0.10 mm                                          |
| Slip resistance                   | EN 13893 DIN 51130   |  | R9                                                 |
| Antistatic                        | EN 1815              |  | Permanent antistatisch                             |
| Light fastness                    | DIN EN ISO 105 B02   |  | ≥ 7                                                |
| Usage classification              | EN ISO 10874 EN 685  |  | 34                                                 |
|                                   |                      |  | 43                                                 |
| Castor chair test (Type W)        | EN ISO 4918 (EN 425) |  | Geschikt voor bureaustoelen met zachte zwenkwielen |
| Light Reflectance Value (LRV - Y) |                      |  | 28.5                                               |

TECHNICAL SPECIFICATIONS

|                              |              |                                                                                     |          |
|------------------------------|--------------|-------------------------------------------------------------------------------------|----------|
| Static electrical propensity | EN 1815      |  | ≤ 2.0 kV |
| Flammability                 | DIN EN 13501 |  | Cfl-s1   |

|                    |          |                                                                                   |                             |
|--------------------|----------|-----------------------------------------------------------------------------------|-----------------------------|
| Thermal resistance | ISO 8302 |  | ca. 0.01 m <sup>2</sup> K/W |
|--------------------|----------|-----------------------------------------------------------------------------------|-----------------------------|

## ENVIRONMENTAL SPECIFICATIONS

|                        |          |                                                                                   |                                                                       |
|------------------------|----------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Formaldehyde emissions | EN 717-1 |  | Complies with European E1 standard (European chamber method EN 717-1) |
|------------------------|----------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------|

|                |                                                                                   |    |
|----------------|-----------------------------------------------------------------------------------|----|
| The Blue Angel |  | Ja |
|----------------|-----------------------------------------------------------------------------------|----|

|                |  |     |
|----------------|--|-----|
| Phthalate free |  | Yes |
|----------------|--|-----|

|               |                                                                                   |                                   |
|---------------|-----------------------------------------------------------------------------------|-----------------------------------|
| VOC emissions |  | A+ émissions dans l'air intérieur |
|               |  | FloorScore                        |
|               |  | M1                                |

|                         |                                                                                   |    |
|-------------------------|-----------------------------------------------------------------------------------|----|
| CO <sub>2</sub> neutral |  | Ja |
|-------------------------|-----------------------------------------------------------------------------------|----|

|            |                                                                                   |    |
|------------|-----------------------------------------------------------------------------------|----|
| Recyclable |  | Ja |
|------------|-----------------------------------------------------------------------------------|----|

|    |                                                                                   |    |
|----|-----------------------------------------------------------------------------------|----|
| CE |  | CE |
|----|-----------------------------------------------------------------------------------|----|

## PRODUCT OPTIONS

|            |
|------------|
| XXtra Care |
|------------|



We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

## LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)