




PURLINE 1500 PSo25 | PURE WHITE |
WELDING RODS

PRODUCT SPECIFICATIONS		
Number of tufts	ISO 1763	o p/m²
Total weight	EN ISO 24340 (EN 429)	 3450 g/m²
Total thickness	EN ISO 24346 (EN 428)	 4.0 mm
Composition	PE	
Manufacturation process	Calender process	
Design	Uni	

PERFORMANCE SPECIFICATIONS		
Dimensional stability	EN ISO 23999	 ≤ 0.15%
Residual indentation	EN ISO 24343-1	 ≤ 0.10 mm
Slip resistance	EN 13893 DIN 51130	 R9
Antistatic	EN 1815	 Permanent antistatisch
Light fastness	DIN EN ISO 105 B02	 ≥ 7
Usage classification	EN ISO 10874 EN 685	 34
		 43
Castor chair test (Type W)	EN ISO 4918 (EN 425)	 Geschikt voor bureaustoelen met zachte zwenkwielen
Light Reflectance Value (LRV - Y)		 82.5

TECHNICAL SPECIFICATIONS

Static electrical propensity	EN 1815		≤ 2.0 kV
Flammability	DIN EN 13501		Cfl-s1
Thermal resistance	ISO 8302		ca. 0.01 m² K/W
Impact sound insulation	ISO 10140		4 dB

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1		Complies with European E1 standard (European chamber method EN 717-1)
The Blue Angel			Ja
Phthalate free			Yes
VOC emissions		  	A+ émissions dans l'air intérieur Floorscore M1
CO ₂ neutral			Ja
Recyclable			Ja
CE			CE

PRODUCT OPTIONS

XXtra Care		We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.
------------	---	--

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leoxx.com | I www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01



[View product](#)