



PURLINE 1500 PS394 | NEWPORT OAK
BROWN | WELDING RODS

PRODUCT SPECIFICATIONS

Total thickness	EN ISO 24346 (EN 428)		4.0 mm
Composition			PE
Manufacturation process			Calender process
Design			Uni

PERFORMANCE SPECIFICATIONS

Dimensional stability	EN ISO 23999		≤ 0.15%
Residual indentation	EN ISO 24343-1		≤ 0.10 mm
Slip resistance	EN 13893 DIN 51130		R9
Antistatic	EN 1815		Permanent antistatisch
Light fastness	DIN EN ISO 105 B02		≥ 7
Usage classification	EN ISO 10874 EN 685		34
			43
Castor chair test (Type W)	EN ISO 4918 (EN 425)		Geschikt voor bureaustoelen met zachte zwenkwielen
Light Reflectance Value (LRV - Y)			30.5

TECHNICAL SPECIFICATIONS

Static electrical propensity	EN 1815		≤ 2.0 kV
Flammability	DIN EN 13501		Cfl-s1

Thermal resistance	ISO 8302		ca. 0.01 m ² K/W
--------------------	----------	---	-----------------------------

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1		Complies with European E1 standard (European chamber method EN 717-1)
------------------------	----------	---	---

The Blue Angel		Ja
----------------	---	----

Phthalate free		Yes
----------------	--	-----

VOC emissions		A+ émissions dans l'air intérieur
		FloorScore
		M1

CO ₂ neutral		Ja
-------------------------	---	----

Recyclable		Ja
------------	---	----


CE		CE
----	---	----

PRODUCT OPTIONS

XXtra Care		We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.
------------	---	--

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)