




SILKY LINE 277 | CARPET 400 CM

PRODUCT SPECIFICATIONS

|                     |              |                                                                                               |
|---------------------|--------------|-----------------------------------------------------------------------------------------------|
| Surface structure   | DIN ISO 2424 | Frisé                                                                                         |
| Pile material       | DIN ISO 2424 | 100% polyamide PA 6.6 Piece Dyed                                                              |
| (Secondary) backing | DIN ISO 2424 | Action back                                                                                   |
| Gauge               |              | 1/10                                                                                          |
| Number of tufts     | ISO 1763     | 312000 p/m²                                                                                   |
| Total weight        | ISO 8543     |  3135 g/m² |
| Total height        | ISO 1765     |  11 mm     |
| Pile weight         | DIN ISO 2424 | 2265 g/m²                                                                                     |
| Pile height         | ISO 1766     | 7.9 mm                                                                                        |
| Design              |              | Uni                                                                                           |
|                     |              | Lineair                                                                                       |

PERFORMANCE SPECIFICATIONS

|                      |                    |                                                                                                                             |
|----------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Comfort level        | EN 1307            |  LC5                                     |
| Usage classification | EN 1307            |  32 - normal project use                 |
| Castor chair test    | EN 985             |  Suitable for office chairs with castors |
| Slip resistance      | EN 13893 DIN 51130 |  Antislip                                |
| Usage on stairs      |                    |  Stair suitable living                   |
| Light fastness       | DIN EN ISO 105 B02 |  4en5                                    |

|                                |                    |                                                                                                          |
|--------------------------------|--------------------|----------------------------------------------------------------------------------------------------------|
| Water fastness                 | DIN EN ISO 105 E01 |  4en5                   |
| Resistance to abrasion dry/wet | DIN EN ISO 105 X12 | 4-5                                                                                                      |
| Antistatic                     | ISO 6356           |  Permanent antistatisch |

## TECHNICAL SPECIFICATIONS

|                          |              |                                                                                                       |
|--------------------------|--------------|-------------------------------------------------------------------------------------------------------|
| Flammability             | DIN EN 13501 |  Cfl-s1              |
| Thermal resistance       | ISO 8302     |  0.17 m² K/W         |
| Impact sound insulation  | ISO 10140    |  35 dB               |
| Acoustical absorption    | ISO 11654    |  0.25 α <sub>w</sub> |
| Sound absorption 125 Hz  | ISO 354      | 0.02 α <sub>s</sub>                                                                                   |
| Sound absorption 250 Hz  | ISO 354      | 0.04 α <sub>s</sub>                                                                                   |
| Sound absorption 500 Hz  | ISO 354      | 0.18 α <sub>s</sub>                                                                                   |
| Sound absorption 1000 Hz | ISO 354      | 0.47 α <sub>s</sub>                                                                                   |
| Sound absorption 2000 Hz | ISO 354      | 0.66 α <sub>s</sub>                                                                                   |
| Sound absorption 4000 Hz | ISO 354      | 0.89 α <sub>s</sub>                                                                                   |

## ENVIRONMENTAL SPECIFICATIONS

|                         |          |                                                                                                                                                           |
|-------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Formaldehyde emissions  | EN 717-1 |  Complies with European E1 standard (European chamber method EN 717-1) |
| GuT                     |          |  GuT-gecertificeerd                                                    |
| CO <sub>2</sub> neutral |          |  Ja                                                                    |
| Recyclable              |          |  Ja                                                                    |
| CE                      |          |  CE                                                                    |

## PRODUCT OPTIONS

|            |                                                                                     |                                                                                                                                                                                                                                                              |
|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| XXtra Care |  | We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor. |
|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## LAYING DIRECTION

### LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leoxx.com | I www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)