



SOLID MIX 718 | TILE 50 X 50 CM

PRODUCT SPECIFICATIONS

|                   |              |                                                                                                                          |
|-------------------|--------------|--------------------------------------------------------------------------------------------------------------------------|
| Surface structure | DIN ISO 2424 | Velours                                                                                                                  |
| Pile material     | DIN ISO 2424 |  100% Econyl (gerecyclede polyamide) SD |
| Gauge             |              | 5/64                                                                                                                     |
| Number of tufts   | ISO 1763     | 255000 p/m²                                                                                                              |
| Total weight      | ISO 8543     |  4270 g/m²                             |
| Total height      | ISO 1765     |  9.8 mm                               |
| Pile weight       | DIN ISO 2424 | 1050 g/m²                                                                                                                |
| Pile height       | ISO 1766     | 4.8 mm                                                                                                                   |
| Design            |              | Gemêleerd                                                                                                                |

PERFORMANCE SPECIFICATIONS

|                                 |                    |                                                                                                                             |
|---------------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Comfort level                   | EN 1307            |  LC3                                     |
| Usage classification            | EN 1307            |  33 - heavy project use                  |
| Castor chair test               | EN 985             |  Suitable for office chairs with castors |
| Fray resistant                  |                    |  Rafelt niet bij het versnijden          |
| Slip resistance                 | EN 13893 DIN 51130 |  Antislip                                |
| Light fastness                  | DIN EN ISO 105 B02 |  ≥ 5                                     |
| Water fastness                  | DIN EN ISO 105 E01 |  ≥ 4                                     |
| Resistance to abraision dry/wet | DIN EN ISO 105 X12 | ≥ 4                                                                                                                         |

|                       |          |                                                                                   |                        |
|-----------------------|----------|-----------------------------------------------------------------------------------|------------------------|
| Antistatic            | ISO 6356 |  | Permanent antistatisch |
| Dimensional stability | EN 986   |  | Falls within norms     |

## TECHNICAL SPECIFICATIONS

|                              |              |                                                                                   |                                 |
|------------------------------|--------------|-----------------------------------------------------------------------------------|---------------------------------|
| Horizontal resistance        | ISO 10965    |                                                                                   | $\leq 10 \cdot 10 \Omega$       |
| Static electrical propensity | EN 1815      |  | $\leq 2.0 \text{ kV}$           |
| Vertical resistance          | ISO 10965    |                                                                                   | $\leq 10 \cdot 10 \Omega$       |
| Flammability                 | DIN EN 13501 |  | Bfl-s1                          |
| Thermal resistance           | ISO 8302     |  | $0.147 \text{ m}^2 \text{ K/W}$ |
| Impact sound insulation      | ISO 10140    |  | 30 dB                           |
| Acoustical absorption        | ISO 11654    |  | 0.30 $\alpha_w$                 |
| Sound absorption 125 Hz      | ISO 354      |                                                                                   | 0.02 $\alpha_s$                 |
| Sound absorption 250 Hz      | ISO 354      |                                                                                   | 0.06 $\alpha_s$                 |
| Sound absorption 500 Hz      | ISO 354      |                                                                                   | 0.21 $\alpha_s$                 |
| Sound absorption 1000 Hz     | ISO 354      |                                                                                   | 0.42 $\alpha_s$                 |
| Sound absorption 2000 Hz     | ISO 354      |                                                                                   | 0.53 $\alpha_s$                 |
| Sound absorption 4000 Hz     | ISO 354      |                                                                                   | 0.64 $\alpha_s$                 |

## ENVIRONMENTAL SPECIFICATIONS

|                         |          |                                                                                     |                                                                       |
|-------------------------|----------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Formaldehyde emissions  | EN 717-1 |  | Complies with European E1 standard (European chamber method EN 717-1) |
| GuT                     |          |  | GuT-gecertificeerd                                                    |
| VOC emissions           |          |  | A+ émissions dans l'air intérieur                                     |
| CO <sub>2</sub> neutral |          |  | Ja                                                                    |
| Recyclable              |          |  | Ja                                                                    |
| CE                      |          |  | CE                                                                    |

## PRODUCT OPTIONS

### LEOXX B.V.

Sasdiijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leox.com | I www.leox.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

## XXtra Care



We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

## LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)

## LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

**T** +31 30 635 10 00 | **E** info@leoxx.com | **I** www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01