



STRUCTURED MESH 952 | CARPET
400 CM

PRODUCT SPECIFICATIONS

Surface structure	DIN ISO 2424		Gestructureerde getufte tip sheared bouclé
Pile material	DIN ISO 2424		100% polyamide 6 Piece Dyed
(Secondary) backing	DIN ISO 2424		Felt backing
Gauge			1/10
Number of tufts	ISO 1763		204880 p/m²
Total weight	ISO 8543		2580 g/m²
Total height	ISO 1765		10 mm
Pile weight	DIN ISO 2424		1180 g/m²
Pile height	ISO 1766		6 mm
Design			Uni Geometrisch

PERFORMANCE SPECIFICATIONS

Comfort level	EN 1307		LC4
Usage classification	EN 1307		33 - heavy project use
Castor chair test	EN 985		Suitable for office chairs with castors
Slip resistance	EN 13893 DIN 51130		Antislip
Usage on stairs			Suitable for stairs
Light fastness	DIN EN ISO 105 B02		≥ 5

Water fastness	DIN EN ISO 105 E01		$\geq 3-4$
Resistance to abrasion dry/wet	DIN EN ISO 105 X12		$\geq 3-4$
Antistatic	ISO 6356		Permanent antistatisch

TECHNICAL SPECIFICATIONS

Horizontal resistance	ISO 10965		$\leq 10 \cdot 11 \Omega$
Vertical resistance	ISO 10965		$\leq 10 \cdot 10 \Omega$
Flammability	DIN EN 13501		Bfl-s1
Thermal resistance	ISO 8302		ca. 0.147 m ² K/W
Impact sound insulation	ISO 10140		31 dB
Static electrical propensity	ISO 6356		$\leq 2.0 \text{ kV}$
Acoustical absorption	ISO 11654		0.35 α_w
Sound absorption 125 Hz	ISO 354		0 as
Sound absorption 250 Hz	ISO 354		0.08 as
Sound absorption 500 Hz	ISO 354		0.35 as
Sound absorption 1000 Hz	ISO 354		0.32 as
Sound absorption 2000 Hz	ISO 354		0.43 as
Sound absorption 4000 Hz	ISO 354		0.5 as

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1		Complies with European E1 standard (European chamber method EN 717-1)
GuT			GuT-gecertificeerd
VOC emissions			A+ émissions dans l'air intérieur
CO ₂ neutral			Ja
Recyclable			Ja
CE			CE

PRODUCT OPTIONS

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leoxx.com | I www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

XXtra Care



We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)

LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | **E** info@leoxx.com | **I** www.leoxx.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01