

SUBTLE NOAH | BROADLOOM 200 CM

PRODUCT SPECIFICATIONS

Surface structure		Jacquard geweven luspool
(Secundary) backing	DIN ISO 2424	Acoustic felt (93% PET)
Number of tufts	ISO 1763	0 p/m²
Total weight	ISO 8543	3750 g/m²
Total height	ISO 1765	4.7 mm
Composition		56% mineral - 10% biobased - 7% recycled - 27% primary fossil content (top layer with fiberglass reinforcing core)
Manufacturation process		Jacquard geweven
Design		Gemêleerd Lineair

PERFORMANCE SPECIFICATIONS

Usage classification	EN 1307	33 - heavy project use
Castor chair test	EN 985	Suitable for office chairs with castors
Fray resistant		Rafelt niet bij het versnijden
Slip resistance	EN 13893 DIN 51130	R10
Usage on stairs		Suitable for stairs
Antistatic	EN 1815	Permanent antistatisch
Light fastness	DIN EN ISO 105 B02	≥ 7
Dimensional stability	EN 986	< 0.2%

LEOXX B.V.
Sasdijk 14, 8281 BM Genemuiden (NL)
T +31 30 635 10 00 | **E** info@leoxx.com | **I** www.leoxx.com
IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

Light Reflectance Value (LRV - Y)	27

TECHNICAL SPECIFICATIONS

Static electrical propensity	EN 1815	< 2.0 kV
Flammability	DIN EN 13501	Bfl-s1
Thermal resistance	ISO 8302	ca. 0.0680 m² K/W
Impact sound insulation	ISO 10140	19 dB
Acoustical absorption	ISO 11654	0.10 αω
Sound absorption 125 Hz	ISO 354	0 αs
Sound absorption 250 Hz	ISO 354	0.03 αs
Sound absorption 500 Hz	ISO 354	0.08 αs
Sound absorption 1000 Hz	ISO 354	0.08 αs
Sound absorption 2000 Hz	ISO 354	0.08 αs
Sound absorption 4000 Hz	ISO 354	0.1 αs

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1	Complies with REACH Complies with European E1 standard (European chamber method EN 717-1)
The Blue Angel		Conform Blauer Engel-normering
Phthalate free		Yes
VOC emissions		A+ émissions dans l'air intérieur Floorscore Indoor Air Comfort Gold M1
CO_2 neutral		Ja
Recyclable		Ja
CE		CE

PRODUCT OPTIONS

XXtra Care	We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.

View product

LEOXX B.V.
Sasdijk 14, 8281 BM Genemuiden (NL)
T +31 30 635 10 00 | **E** info@leoxx.com | **I** www.leoxx.com
IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01