

UNIQUE STONE 10052 | 100X100 CM

PRODUCT SPECIFICATIONS

Finishing	Vellingkanten		
Surface structure	Registered embossed		
Total weight	EN ISO 24340 (EN 429)		4315 g/m²
Total thickness	EN ISO 24346 (EN 428)		2.5 mm
Wear layer thickness	EN ISO 24340 (EN 429)		0.55 mm
Design	Steen		

PERFORMANCE SPECIFICATIONS

Dimensional stability	EN ISO 23999		≤ 0.10%
Residual indentation	EN ISO 24343-1		≤ 0.10 mm
Slip resistance	EN 13893 DIN 51130		R9
Light fastness	DIN EN ISO 105 Bo2		≥ 6
Usage classification	EN ISO 10874 EN 685	 	33 42
Castor chair test (Type W)	EN ISO 4918 (EN 425)	Geschikt voor bureaustoelen met type W	

TECHNICAL SPECIFICATIONS

Flammability	DIN EN 13501		Bfl-s1
Thermal resistance	EN 12664		0.020 m² K/W

ENVIRONMENTAL SPECIFICATIONS

CE	 CE
----	--

LAYING DIRECTION

LEOXX reserves the right to make technical adjustments that lead to quality improvement.