



VIVID LOOP 824 | CUSTOM RUG

PRODUCT SPECIFICATIONS

|                     |              |                                                                                               |
|---------------------|--------------|-----------------------------------------------------------------------------------------------|
| Surface structure   | DIN ISO 2424 | Bouclé                                                                                        |
| Pile material       | DIN ISO 2424 | 100% polyamide 6 Piece Dyed                                                                   |
| Finishing           |              | Maatwerk                                                                                      |
| (Secondary) backing | DIN ISO 2424 | Action back                                                                                   |
| Gauge               |              | 5/32                                                                                          |
| Number of tufts     | ISO 1763     | 100800 p/m²                                                                                   |
| Total weight        | ISO 8543     |  1790 g/m² |
| Total height        | ISO 1765     |  9 mm      |
| Pile weight         | DIN ISO 2424 | 790 g/m²                                                                                      |
| Pile height         | ISO 1766     | 7 mm                                                                                          |
| Design              |              | Uni<br>Abstract                                                                               |

PERFORMANCE SPECIFICATIONS

|                      |                    |                                                                                                                             |
|----------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Comfort level        | EN 1307            |  LC2                                     |
| Usage classification | EN 1307            |  33 - heavy project use                  |
| Castor chair test    | EN 985             |  Suitable for office chairs with castors |
| Slip resistance      | EN 13893 DIN 51130 |  Antislip                                |
| Light fastness       | DIN EN ISO 105 B02 |  ≥ 5                                     |
| Water fastness       | DIN EN ISO 105 E01 |  ≥ 4                                     |

|                                |                    |                                                                                                          |
|--------------------------------|--------------------|----------------------------------------------------------------------------------------------------------|
| Resistance to abrasion dry/wet | DIN EN ISO 105 X12 | ≥ 4                                                                                                      |
| Antistatic                     | ISO 6356           |  Permanent antistatisch |

## TECHNICAL SPECIFICATIONS

|                          |              |                                                                                           |
|--------------------------|--------------|-------------------------------------------------------------------------------------------|
| Flammability             | DIN EN 13501 |  Cfl-s1  |
| Impact sound insulation  | ISO 10140    |  26 dB   |
| Acoustical absorption    | ISO 11654    |  0.15 αω |
| Sound absorption 125 Hz  | ISO 354      | 0 αs                                                                                      |
| Sound absorption 250 Hz  | ISO 354      | 0.05 αs                                                                                   |
| Sound absorption 500 Hz  | ISO 354      | 0.05 αs                                                                                   |
| Sound absorption 1000 Hz | ISO 354      | 0.2 αs                                                                                    |
| Sound absorption 2000 Hz | ISO 354      | 0.4 αs                                                                                    |
| Sound absorption 4000 Hz | ISO 354      | 0.6 αs                                                                                    |

## ENVIRONMENTAL SPECIFICATIONS

|                         |          |                                                                                                                                                                                                                                      |
|-------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Formaldehyde emissions  | EN 717-1 |  Complies with European E1 standard (European chamber method EN 717-1)                                                                            |
| GuT                     |          |  GuT-gecertificeerd                                                                                                                               |
| The Blue Angel          |          |  Ja                                                                                                                                               |
| VOC emissions           |          |  A+ émissions dans l'air intérieur<br> Indoor Air Comfort Gold |
| CO <sub>2</sub> neutral |          |  Ja                                                                                                                                               |
| Recyclable              |          |  Ja                                                                                                                                               |
| CE                      |          |  CE                                                                                                                                               |

## PRODUCT OPTIONS

|            |                                                                                     |                                                                                                                                                                                                                                                              |
|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| XXtra Care |  | We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor. |
|------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### LEOXX B.V.

Sasdijk 14, 8281 BM Genemuiden (NL)

T +31 30 635 10 00 | E info@leox.com | I www.leox.com

IBAN NL87 RABO 0305 9745 13 | KvK 30151348 | BTW NL807305157B01

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)