




WOVEN STRIPES 984 | CUSTOM RUG

PRODUCT SPECIFICATIONS

Surface structure	DIN ISO 2424	Vlak geweven luspool
Pile material	DIN ISO 2424	 100% Econyl (gerecyclede polyamide) PD
Finishing		Maatwerk
(Secondary) backing	DIN ISO 2424	Action back
Number of tufts	ISO 1763	o p/m²
Total weight	ISO 8543	 2400 g/m²
Total height	ISO 1765	 4 mm
Pile weight	DIN ISO 2424	785 g/m²
Pile height	ISO 1766	2 mm
Design		Lineair

PERFORMANCE SPECIFICATIONS

Comfort level	EN 1307	 LC1
Usage classification	EN 1307	 33 - heavy project use
Castor chair test	EN 985	 Suitable for office chairs with castors
Slip resistance	EN 13893 DIN 51130	 Antislip
Antistatic	ISO 6356	 Permanent antistatisch

TECHNICAL SPECIFICATIONS

Horizontal resistance	ISO 10965	3.4 X 10 ⁻¹² Ω
-----------------------	-----------	---------------------------

Vertical resistance	ISO 10965		1.4 X 10 ⁻¹² Ω
Flammability	DIN EN 13501		Cfl-s1
Impact sound insulation	ISO 10140		17 dB
Static electrical propensity	ISO 6356		< 1.5 kV
Acoustical absorption	ISO 11654		0.15 αω

ENVIRONMENTAL SPECIFICATIONS

Formaldehyde emissions	EN 717-1		Complies with European E1 standard (European chamber method EN 717-1)
GuT			Geproduceerd conform GUT normeringen
VOC emissions			Indoor Air Comfort Gold
CO ₂ neutral			Ja
Recyclable			Ja
CE			CE

PRODUCT OPTIONS

XXtra Care		We like to keep our floors beautiful for as long as possible. With XXtra Care we offer everyone with a LEOXX floor a periodical maintenance concept, matching the floor and its function. Ask about the possibilities and extend the lifespan of your floor.
------------	---	--

LEOXX reserves the right to make technical adjustments that lead to quality improvement.



[View product](#)